

Restore 30X™

Accelerated Smoke Damage Restoration

Easily transported to the job site.



30X System

- **O₂ Feedstock Module**
 - Dries, Concentrates, Pumps Air & O₂
 - 68 lbs w/case 20.3" w, 30" h, 12.8" d
- **O₃ Generator**
 - Generates and pumps up to 30,000 mg of pure ozone per hour; requires feedstock
 - 37 lbs w/case 25" w, 12.8" h, 20.3" d
- **Accessories Included**
 - 100 feet of teflon lined polyethylene tubing
 - Manifolds to permit simultaneous treatment of up to nine rooms

For Information Contact

John Edwards

MicroSweep Corp.

Sarasota, FL 34240

Phone: 941-376-9800 Fax 941-377-7295

Email: sales@microsweep.com

MicroSweep

Decontamination Equipment

Powerful Ozone Output for Fire & Smoke Restoration

- **Powerful Ozone Output**
 - Corona discharge raises the concentration of a cubic meter test chamber to 170 ppm in under 6 minutes (results above, right bottom)
 - Eradicates Smoke & Fire Damage Odor
 - Kills Airborne Mold, Bacteria, and Viruses, including MRSA
 - Piped to multiple treatment rooms via special hose and cascade manifolds
- **Easy To Set Up And Operate**
 - O₃ Generator draws power and feed gas from O₂ Feedstock Module
 - Simple controls, interconnections between units. Output flow control dial.
 - On-Off Switches. Uses local 120 Volt AC, 60 hz power.
 - Circuit breaker/fuse with lights.
 - Both units display output gauges, are self cooling.
- **Completely Portable**
 - Transport Cases - Waterproof, heavy duty ABS plastic, colors molded in
 - Hermetic seal, silicone O-ring, pressure equalization valve, removable cover
 - Military style twist-draw latches; three spring-loaded lift handles
 - Collapsible pull handle with recessed wheels; Easy transport

Availability - Delivery in two weeks unless in stock.